



Light Shadow Adjustable Trim Dali Version 2 Spots Optic Spot

■ 03.8885.40ADA - White/Black

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	437
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle:	10°		
	h(m)	E(lx)	D(m)
	1	7883	0.18
	2	1971	0.36
	3	876	0.54
	4	493	0.72
	5	315	0.90

Luminous flux luminaire
437 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable DALI		

Physical

Color	White/Black	Tilt (°)	30
Orientation	Adjustable	Length (mm)	86
Trim	yes		
Recessed depth (mm)	150		
Weight (kg)	0.25		

Note

Pre-Installation frame not required.