


Light Shadow Adjustable Trim Dali Version 2 Spots Optic Spot

■ 03.8888.14ADA - Black/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	475
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle: 10°

h(m)	E(lx)	D(m)
1	8680	0.17
2	2170	0.35
3	964	0.52
4	543	0.70
5	347	0.87

Luminous flux luminaire
475 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

Physical

Color	Black/White	Tilt (°)	30
Orientation	Adjustable	Length (mm)	86
Trim	yes		
Recessed depth (mm)	150		
Weight (kg)	0.25		

Note

Pre-Installation frame not required.