

Light Shadow Adjustable Trim Dali Version 4 Spots Optic Flood

■ 03.9326.40ADA - White/Black

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|---------------------|
| Number of heads | 1 | Net lumen (lm) | 720 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 10.8W | Environment | Indoor dry location |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical


| | |
|-------------------------------|-----------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Flood |
| Beam angle (°) | 33 |
| Beam angle C90-270 (°) | 33 |



Beam Angle: 33°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1 | 2250 | 0.60 |
| 2 | 563 | 1.19 |
| 3 | 250 | 1.79 |
| 4 | 141 | 2.39 |
| 5 | 90 | 2.99 |

Luminous flux luminaire
720 lm (EXTREME CUT OFF)



Electrical

| | | | |
|-----------------------|-----------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | Yes | | |
| Driver | Remote included | | |
| Driver type | Dimmable DALI | | |
| | 1 | | |

Physical

| | | | |
|----------------------------|-------------|--------------------|-----|
| Color | White/Black | Tilt (°) | 30 |
| Orientation | Adjustable | Length (mm) | 156 |
| Trim | yes | | |
| Recessed depth (mm) | 75 | | |
| Weight (kg) | 0.34 | | |

Note

Pre-Installation frame not required.

