



Light Shadow Adjustable Trim Dali Version 4 Spots Optic Spot

03.8896.40ADA - White/White

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	801
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Beam Angle:	10°		
	h(m)	E(lx)	D(m)
	1	14660	0.17
	2	3665	0.35
	3	1629	0.52
	4	916	0.70
	5	586	0.87

Luminous flux luminaire
801 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote included		
Driver type	Dimmable DALI		
	1		

Physical

Color	White/White	Tilt (°)	30
Orientation	Adjustable	Length (mm)	156
Trim	yes		
Recessed depth (mm)	75		
Weight (kg)	0.34		

Note

Pre-Installation frame not required.