

## Light Shadow Adjustable Trim Dali Version 8 Spots Optic Flood

■ □ 03.9355.14ADA - Black/White

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	1872
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	21.6W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		


### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	33
<b>Beam angle C90-270 (°)</b>	33



<b>Beam Angle:</b>	33°		
	<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	5835	0.59	
2	1459	1.18	
3	648	1.78	
4	365	2.37	
5	233	2.96	

Luminous flux luminaire  
1872 lm (EXTREME CUT OFF)



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote included		
<b>Driver type</b>	Dimmable DALI		
	1		

### Physical

<b>Color</b>	Black/White	<b>Tilt (°)</b>	30
<b>Orientation</b>	Adjustable	<b>Length (mm)</b>	296
<b>Trim</b>	yes		
<b>Recessed depth (mm)</b>	75		
<b>Weight (kg)</b>	0.50		

### Note

Pre-Installation frame not required.

