

## Light Shadow DOTS - Single Spot Module. Set of 1 Spot

03.8600.40A - White




LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	188
<b>Lamp category</b>	LED	<b>Mountings</b>	Recessed
<b>Power (W)</b>	2.7W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Spot
<b>Beam angle (°)</b>	10
<b>Beam angle C90-270 (°)</b>	10



Beam Angle: 10°

h(m)	E(lx)	D(m)
1	3436	0.17
2	859	0.35
3	382	0.52
4	215	0.70
5	137	0.87

Luminous flux luminaire  
188 lm (EXTREME CUT OFF)



### Electrical

<b>Voltage (V)</b>	3	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic, Electronic dimmable 1-10V, Electronic dimmable DALI		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	75
<b>Weight (kg)</b>	0.05
<b>Spot diameter (mm)</b>	32.5



## Light Shadow DOTS - Single Spot Module. Set of 1 Spot



Pre-installation frame. 1L  
08.0580.00



70 mm divider to keep the spacing  
between spots when putting together  
70 mm modules  
08.0586.00



Non dimmable continuous current  
power supply of 15-20W, 110/240V –  
50/60Hz, with power current selected  
through adjustable 350 mA-15W /500  
mA / 550 / 700 / 850 mA / 900 mA – 20W  
switch  
60.8911



Non dimmable continuous current  
power supply of 20W, dimmable 0-10V,  
220/240V – 50/60Hz  
60.9414



Continuous current power supply of  
20W, dimmable DALI 2, 220/240V –  
50/60Hz with power current 900 mA.  
60.9415



Continuous current power supply,  
dimmable Casambi, 220/240V –  
50/60Hz, 300mA-16W / 350mA-18,5W /  
400mA-21,5W / 450mA-24W / 500mA-  
27W / 600mA-32W / 650mA-35W /  
700mA-36W / 750/800/900/1000/1050mA  
– 38W  
60.9207