

## Light Shadow DOTS - Single Spot Module. Set of 2 Spots

03.8644.40A - White




LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 2     | Net lumen (lm) | 397                 |
| Lamp category   | LED   | Mountings      | Recessed            |
| Power (W)       | 5.4W  | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 22        |
| Beam angle C90-270 (°) | 22        |



Beam Angle: 22°

h(m) E(lx) D(m)

1 2651 0.39


2 663 0.78

3 295 1.17

4 166 1.56

5 106 1.95

Luminous flux luminaire  
397 lm




### Electrical

|              |                                                                 |                  |         |
|--------------|-----------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 2x3                                                             | Emergency        | Without |
| Current (mA) | 900                                                             | Insulation class | III     |
| Dimmable     | Yes                                                             |                  |         |
| Driver       | Remote excluded                                                 |                  |         |
| Driver type  | Non Dimmable, Dimmable 0-10V, Dimmable Casambi, Dimmable DALI 1 |                  |         |

### Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Orientation         | Fixed |
| Recessed depth (mm) | 75    |
| Weight (kg)         | 0.10  |
| Spot diameter (mm)  | 32.5  |



Light Shadow DOTS - Single Spot Module. Set of 2 Spots



Pre-installation frame. 2L – int 43  
08.0581.00



Pre-installation frame. 2L – int 70  
08.0583.00



70 mm divider to keep the spacing  
between spots when putting together  
70 mm modules  
08.0586.00



Non dimmable continuous current  
power supply of 20W, dimmable 0-10V,  
220/240V – 50/60Hz  
60.9414



Continuous current power supply,  
dimmable Casambi 220/240V-50/60Hz,  
300mA-16W / 350mA-18,5W / 400mA-  
21,5W / 450mA-24W / 500mA-27W /  
600mA-32W / 650mA-35W / 700mA-36W  
/750/800/900/1000/1050mA – 38W  
60.9207



Non dimmable continuous current  
power supply of 15-20W, 110/240V –  
50/60Hz, with power current selected  
through adjustable 350 mA-15W / 500  
mA / 550 / 700 / 850 mA / 900 mA – 20W  
switch  
60.8911



300mA-13W / 350mA-15W / 400mA-18W  
/ 450mA-20W / 500mA-22W / 550mA-  
24W / 600mA-27W / 650mA-29W /  
700mA-31W / 750mA-32W / 800mA-33W  
/ 850mA-35W / 900mA-38W / 950mA-  
40W / 1000/1050mA-42W  
60.9162