

Light Shadow DOTS - Single Spot Module. Set of 2 Spots**■ 03.8645.14A - Black**


LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

**Main specifications**

Number of heads	2	Net lumen (lm)	384
Lamp category	LED	Mountings	Recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical


Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	1200	0.60
2	300	1.19
3	133	1.79
4	75	2.39
5	48	2.99


Luminous flux luminaire
384 lm

**Electrical**

Voltage (V)	2x3	Emergency	Without
Current (mA)	900	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable 0-10V, Dimmable Casambi, Dimmable DALI 1		

Physical

Color	Black
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.10
Spot diameter (mm)	32.5



Light Shadow DOTS - Single Spot Module. Set of 2 Spots



Non dimmable continuous current power supply of 15-20W, 110/240V – 50/60Hz, with power current selected through adjustable 350 mA-15W /500 mA/ /550 / 700 / 850 mA / 900 mA – 20W switch

60.8911



Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W

60.9162



Pre-installation frame. 2L – int 70

08.0583.00



70 mm divider to keep the spacing between spots when putting together 70 mm modules

08.0586.00



Non dimmable continuous current power supply of 20W, dimmable 0-10V, 220/240V – 50/60Hz

60.9414



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W

60.9207



Pre-installation frame. 2L – int 43
08.0581.00