

Light Shadow DOTS - Single Spot Module. Set of 2 Spots

03.8646.06A - Chrome



LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.


Main specifications

Number of heads	1	Net lumen (lm)	370
Lamp category	LED	Mountings	Recessed
Power (W)	5.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		




Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	44
Beam angle C90-270 (°)	44



Beam Angle:	44°		
h(m)	E(lx)	D(m)	
1	771	0.80	
2	193	1.60	
3	86	2.40	
4	48	3.19	
5	31	3.99	

Luminous flux luminaire
370 lm




Electrical

Voltage (V)	3	Insulation class	III
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic, Electronic dimmmable 1- 10V, Electronic dimmmable DALI		
Emergency	Without		

Physical

Color	Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.10
Spot diameter (mm)	32.5



Light Shadow DOTS - Single Spot Module. Set of 2 Spots



Pre-installation frame. 2L – int 43
08.0581.00



Pre-installation frame. 2L – int 70
08.0583.00



70 mm divider to keep the spacing between spots when putting together 70 mm modules
08.0586.00



Non dimmable continuous current power supply of 15-20W, 110/240V – 50/60Hz, with power current selected through adjustable switch
60.8911



Continuous current power supply 220/240V – 50/60Hz. Adjustable Current
300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W
60.9162



Non dimmable continuous current power supply of 20W, dimmable 0-10V, 220/240V – 50/60Hz
60.9414



Continuous current power supply of
20W, dimmable DALI 2, 220/240V –
50/60Hz with power current 900 mA.
60.9415

Continuous current power supply,
dimmable Casambi, 220/240V –
50/60Hz, 300mA-16W / 350mA-18,5W /
400mA-21,5W / 450mA-24W / 500mA-
27W / 600mA-32W / 650mA-35W /
700mA-36W / 750/800/900/1000/1050mA
– 38W
60.9207