

Light Shadow DOTS - Single Spot Module. Set of 2 Spots**03.8647.06A - Chrome**


LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

Main specifications

Number of heads	2	Net lumen (lm)	394
Lamp category	LED	Mountings	Recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	44
Beam angle C90-270 (°)	44



Beam Angle: 44°

h(m)	E(lx)	D(m)
------	-------	------

1	822	0.80
---	-----	------

2	206	1.60
---	-----	------

3	91	2.40
---	----	------

4	51	3.19
---	----	------

5	33	3.99
---	----	------



Luminous flux luminaire
394 lm

Electrical

Voltage (V)	2x3	Emergency	Without
Current (mA)	900	Insulation class	III
Dimmable	Yes		
Driver	Remote excluded		
Driver type	Non Dimmable, Dimmable 0-10V, Dimmable Casambi, Dimmable DALI 1		

Physical

Color	Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.10
Spot diameter (mm)	32.5



Light Shadow DOTS - Single Spot Module. Set of 2 Spots



70 mm divider to keep the spacing between spots when putting together 70 mm modules
08.0586.00



Non dimmable continuous current power supply of 15-20W, 110/240V – 50/60Hz, with power current selected through adjustable 350 mA-15W /500 mA/ /550 / 700 / 850 mA / 900 mA – 20W switch
60.8911



Pre-installation frame. 2L – int 43
08.0581.00



Pre-installation frame. 2L – int 70
08.0583.00



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W
60.9207



Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W
60.9162



Non dimmable continuous current
power supply of 20W, dimmable 0-10V,
220/240V – 50/60Hz
60.9414