

## Light Shadow DOTS - Single Spot Module. Set of 4 Spots

03.8611.40A - White



LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.


### Main specifications

<b>Number of heads</b>	4	<b>Net lumen (lm)</b>	744
<b>Lamp category</b>	LED	<b>Mountings</b>	Recessed
<b>Power (W)</b>	10.8W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		




### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	22
<b>Beam angle C90-270 (°)</b>	22



<b>Beam Angle:</b>	22°	
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>
1	4970	0.39
2	1243	0.78
3	552	1.17
4	311	1.56
5	199	1.95

Luminous flux luminaire  
744 lm



### Electrical

<b>Voltage (V)</b>	4x3	<b>Emergency</b>	Without
<b>Current (mA)</b>	900	<b>Insulation class</b>	III
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote excluded		
<b>Driver type</b>	Non Dimmable, Dimmable 0-10V, Dimmable Casambi, Dimmable DALI		
	1		

### Physical

<b>Color</b>	White
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	75
<b>Weight (kg)</b>	0.20
<b>Spot diameter (mm)</b>	32.5



## Light Shadow DOTS - Single Spot Module. Set of 4 Spots




---

Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207

---

Non dimmable continuous current power supply of 20W, dimmable 0-10V, 220/240V – 50/60Hz  
60.9414

---

70 mm divider to keep the spacing between spots when putting together 70 mm modules  
08.0586.00




---

Pre-installation frame. 4L – int 70  
08.0584.00

---

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W  
60.9162

---

Non dimmable continuous current power supply of 15-20W, 110/240V – 50/60Hz, with power current selected through adjustable 350 mA-15W / 500 mA / 550 / 700 / 850 mA / 900 mA – 20W switch  
60.8911



---

Pre-installation frame. 4L – int 43  
08.0582.00