

## Light Shadow DOTS - Single Spot Module. Set of 4 Spots

03.8612.40A - White




LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 4     | Net lumen (lm) | 741                 |
| Lamp category   | LED   | Mountings      | Recessed            |
| Power (W)       | 10.8W | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 33        |
| Beam angle C90-270 (°) | 33        |



Beam Angle: 33°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 2310  | 0.59 |
| 2    | 577   | 1.18 |
| 3    | 257   | 1.78 |
| 4    | 144   | 2.37 |
| 5    | 92    | 2.96 |

Luminous flux luminaire  
741 lm




### Electrical

|              |                                                                 |                  |         |
|--------------|-----------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 4x3                                                             | Emergency        | Without |
| Current (mA) | 900                                                             | Insulation class | III     |
| Dimmable     | Yes                                                             |                  |         |
| Driver       | Remote excluded                                                 |                  |         |
| Driver type  | Non Dimmable, Dimmable 0-10V, Dimmable Casambi, Dimmable DALI 1 |                  |         |

### Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Orientation         | Fixed |
| Recessed depth (mm) | 75    |
| Weight (kg)         | 0.20  |
| Spot diameter (mm)  | 32.5  |



# Light Shadow DOTS - Single Spot Module. Set of 4 Spots



Pre-installation frame. 4L – int 43  
08.0582.00

Pre-installation frame. 4L – int 70  
08.0584.00

70 mm divider to keep the spacing  
between spots when putting together  
70 mm modules  
08.0586.00



Non dimmable continuous current  
power supply of 20W, dimmable 0-10V,  
220/240V – 50/60Hz  
60.9414

Continuous current power supply,  
dimmable Casambi 220/240V-50/60Hz,  
300mA-16W / 350mA-18,5W / 400mA-  
21,5W / 450mA-24W / 500mA-27W /  
600mA-32W / 650mA-35W / 700mA-36W  
/750/800/900/1000/1050mA – 38W  
60.9207

Non dimmable continuous current  
power supply of 15-20W, 110/240V –  
50/60Hz, with power current selected  
through adjustable 350 mA-15W /500  
mA/ /550 / 700 / 850 mA / 900 mA – 20W  
switch  
60.8911



300mA-13W / 350mA-15W / 400mA-18W  
/ 450mA-20W / 500mA-22W / 550mA-  
24W / 600mA-27W / 650mA-29W /  
700mA-31W / 750mA-32W / 800mA-33W  
/ 850mA-35W / 900mA-38W / 950mA-  
40W / 1000/1050mA-42W  
60.9162