

## Light Shadow DOTS - Single Spot Module. Set of 4 Spots

■ 03.8614.14A - Black




LED lighting module, with low glare, to be inserted in the recessed frames (not included), installation through a bayonet system with interchangeable spots. Available in one-light versions and groups of two and four lights. Driver not included, the driver has to be directly connected to the embedding frames.

### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 4     | Net lumen (lm) | 793                 |
| Lamp category   | LED   | Mountings      | Recessed            |
| Power (W)       | 10.8W | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical


|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Medium    |
| Beam angle (°)         | 22        |
| Beam angle C90-270 (°) | 22        |



Beam Angle: 22°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 | 5425 | 0.39  |      |
| 2 | 1356 | 0.78  |      |
| 3 | 603  | 1.17  |      |
| 4 | 339  | 1.56  |      |
| 5 | 217  | 1.95  |      |

Luminous flux luminaire  
793 lm




### Electrical

|              |                                                                 |                  |         |
|--------------|-----------------------------------------------------------------|------------------|---------|
| Voltage (V)  | 4x3                                                             | Emergency        | Without |
| Current (mA) | 900                                                             | Insulation class | III     |
| Dimmable     | Yes                                                             |                  |         |
| Driver       | Remote excluded                                                 |                  |         |
| Driver type  | Non Dimmable, Dimmable 0-10V, Dimmable Casambi, Dimmable DALI 1 |                  |         |

### Physical

|                     |       |
|---------------------|-------|
| Color               | Black |
| Orientation         | Fixed |
| Recessed depth (mm) | 75    |
| Weight (kg)         | 0.20  |
| Spot diameter (mm)  | 32.5  |



## Light Shadow DOTS - Single Spot Module. Set of 4 Spots



Non dimmable continuous current power supply of 20W, dimmable 0-10V, 220/240V – 50/60Hz  
60.9414



Continuous current power supply, dimmable Casambi 220/240V-50/60Hz, 300mA-16W / 350mA-18,5W / 400mA-21,5W / 450mA-24W / 500mA-27W / 600mA-32W / 650mA-35W / 700mA-36W / 750/800/900/1000/1050mA – 38W  
60.9207



Pre-installation frame. 4L – int 43  
08.0582.00



Non dimmable continuous current power supply of 15-20W, 110/240V – 50/60Hz, with power current selected through adjustable 350 mA-15W / 500 mA / 550 / 700 / 850 mA / 900 mA – 20W switch  
60.8911



Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W  
60.9162



Pre-installation frame. 4L – int 70  
08.0584.00



---

70 mm divider to keep the spacing  
between spots when putting together  
70 mm modules  
08.0586.00