


## Light Shadow Fixed No Trim 12 Spots Optic Flood

03.9267.14A - Black/Chrome

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 2728                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 32.4W | Environment    | Indoor dry location |
| CCT (K)         | 2700K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Flood     |
| Beam angle (°)         | 33        |
| Beam angle C90-270 (°) | 33        |



Beam Angle: 33°

|   | h(m) | E(lx) | D(m) |
|---|------|-------|------|
| 1 |      | 8449  | 0.60 |
| 2 |      | 2112  | 1.19 |
| 3 |      | 939   | 1.79 |
| 4 |      | 528   | 2.38 |
| 5 |      | 338   | 2.98 |

Luminous flux luminaire  
2728 lm (EXTREME CUT OFF)

### Electrical

|                |                 |                  |    |
|----------------|-----------------|------------------|----|
| Frequency (Hz) | 50/60           | Insulation class | II |
| Voltage (V)    | 220.00          |                  |    |
| Dimmable       | No              |                  |    |
| Driver         | Remote included |                  |    |
| Emergency      | Without         |                  |    |

### Physical

|                     |              |
|---------------------|--------------|
| Color               | Black/Chrome |
| Orientation         | Fixed        |
| Recessed depth (mm) | 75           |
| Weight (kg)         | 0.66         |
| Length (mm)         | 420          |

### Note

It requires a pre-installation frame, to be ordered separately.



# Light Shadow Fixed No Trim 12 Spots Optic Flood



---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90

---

Pre-installation Frame  
08.0513.00