


Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).











 Number of heads
 1

 Lamp category
 LED

 Power (W)
 32.4W

 CCT (K)
 2700K


 CRI
 90

Net lumen (lm) Mountings Environment 2736 Ceiling

Ceiling recessed Indoor dry location

### Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Spot
Beam angle (°) 10
Beam angle C90-270 (°) 10



Luminous flux luminaire 2736 lm (EXTREME CUT OFF)

Insulation class

Ве	am	10°	
h(n	n)	E(lx)	D(m)
1_	4	8193	0.18
2	1.	2048	0.36
3		5355	0.55

3012

1928

0.73

0.91

## Electrical

 Frequency (Hz)
 50/60

 Voltage (V)
 220.00

 Dimmable
 No

 Driver
 Remote

Driver Remote included Emergency Without

#### Physical

Color Black/Chrome
Orientation Fixed
Recessed depth (mm) 75
Weight (kg) 0.66
Length (mm) 420

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 12 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0052.90 Pre-installation Frame 08.0513.00