




03.8878.40A - White/Chrome

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).









Main specifications


Number of heads LED Lamp category Power (W) 32.4W CCT (K) 2700K CRI 90

Net lumen (lm) 2736 Mountings

Ceiling recessed Environment Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10



Luminous flux luminaire 2736 lm (EXTREME CUT OFF)

Insulation class

Beam Angle:			10°
h(n	า)	E(lx)	D(m)
1_	48	193	0.18
2	120	048	0.36
3	53	355	0.55
4	30	012	0.73

1928

0.91

5

Electrical

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No

Driver Remote included **Emergency**

Without

Physical

Color White/Chrome Orientation Fixed Recessed depth (mm) 75 Weight (kg) 0.66 Length (mm) 420

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 12 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0513.00