




03.8881.40A - White/Black


Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).












Number of neads	I
Lamp category	LED
Power (W)	32.4W
CCT (K)	3000K
CRI	90

Net lumen (lm) Mountings Environment 2773 Ceiling re

Ceiling recessed Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire 2773 lm (EXTREME CUT OFF)

Insulation class

Beam Angle:		10°
h(n	n) E(l x)	D(m)
1_	50052	0.18
2	12513	0.36
3	5561	0.54
4	3128	0.72
5	2002	0.90

Electrical

Physical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Remote include

Driver Remote include Emergency Without

ColorWhite/BlackOrientationFixedRecessed depth (mm)75Weight (kg)0.66Length (mm)420

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 12 Spots Optic Spot





Pre-installation Frame 08.0513.00

Accessory for mounting of No Trim continuous line. 08.0052.90