


Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).











		• • • • •
11./	าวเก	specifications
IV	ıaııı	SUCCINCATIONS

Number of heads	1	
Lamp category	LED	
Power (W)	32.4W	
CCT (K)	3000K	
CPI	90	


Net lumen (lm) Mountings Environment

2888

Ceiling recessed Indoor dry location

#### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire 2888 lm (EXTREME CUT OFF)

Вe	am Angle:	10-
h(r	n) E(lx)	D(m)
1_	50870	0.18
2	12718	0.36
3	5652	0.55
4	3179	0.73
5	2035	0.91

### **Electrical**

Frequency (Hz)	50/60	Insulation class	П
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		

Without

## **Emergency** Physical

Color	Black/Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.66
Length (mm)	420

### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 12 Spots Optic Spot





Pre-installation Frame 08.0513.00

Accessory for mounting of No Trim continuous line. 08.0052.90