




## 03.8374.40A - White/White

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).









Main specifications
---------------------

Number of heads LED Lamp category Power (W) 32.4W CCT (K) 2700K CRI 90


Net lumen (lm) Mountings Environment

2652

Ceiling recessed Indoor dry location

### Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Wide flood Beam angle (°) 45 Beam angle C90-270 (°) 45



Luminous flux luminaire 2652 lm (EXTREME CUT OFF)

Insulation class

Beam Angle:		45°
h(m)	E(lx)	D(m)
1	4942	0.83
2	1235	1.67
3	549	2.50
4	309	3.34

198

4.17

5

### **Electrical**

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No Driver

Remote included **Emergency** 

Without

### Physical

Color White/White Orientation Fixed Recessed depth (mm) 75 Weight (kg) 0.66 Length (mm) 420

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 12 Spots Optic Wide Flood





Accessory for mounting of No Trim continuous line. 08.0052.90 Pre-installation Frame 08.0513.00