




## Light Shadow Fixed No Trim 12 Spots Optic Wide Flood

03.8379.14A - Black/Black

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

Number of heads	1	Net lumen (lm)	2815
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle: 46°

h(m)	E(lx)	D(m)
1	5339	0.84
2	1335	1.69
3	593	2.53
4	334	3.38
5	214	4.22

Luminous flux luminaire  
2815 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

### Physical


Color	Black/Black
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.66
Length (mm)	420

### Note

It requires a pre-installation frame, to be ordered separately.



# Light Shadow Fixed No Trim 12 Spots Optic Wide Flood



---

Pre-installation Frame  
08.0513.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90