


## Light Shadow Fixed No Trim 2 Spots Optic Flood

■ 03.9215.14A - Black/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

Number of heads	1	Net lumen (lm)	468
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	1459	0.59
2	365	1.18
3	162	1.78
4	91	2.37
5	58	2.96

Luminous flux luminaire  
468 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

### Physical


Color	Black/White
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

### Note

It requires a pre-installation frame, to be ordered separately.



# Light Shadow Fixed No Trim 2 Spots Optic Flood



Accessory for mounting of No Trim  
continuous line.  
08.0052.90

Pre-installation Frame  
08.0510.00