



Light Shadow Fixed No Trim 2 Spots Optic Flood

03.9218.40A - White/Gold


Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).

**Main specifications**

Number of heads	1	Net lumen (lm)	462
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	1423	0.60
2	356	1.20
3	158	1.79
4	89	2.39
5	57	2.99

Luminous flux luminaire
462 lm (EXTREME CUT OFF)**Electrical**

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		


Physical

Color	White/Gold
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 2 Spots Optic Flood



Pre-installation Frame
08.0510.00

Accessory for mounting of No Trim
continuous line.
08.0052.90