




## Light Shadow Fixed No Trim 2 Spots Optic Medium

03.9203.40A - White/Gold

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	445
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	5.4W	<b>Environment</b>	Indoor dry location
<b>CCT (K)</b>	2700K		
<b>CRI</b>	90		

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Medium
<b>Beam angle (°)</b>	22
<b>Beam angle C90-270 (°)</b>	22



<b>Beam Angle:</b>	22°		
<b>h(m)</b>	<b>E(lx)</b>	<b>D(m)</b>	
1	2976	0.39	
2	744	0.78	
3	331	1.17	
4	186	1.56	
5	119	1.95	

Luminous flux luminaire  
445 lm (EXTREME CUT OFF)

### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Insulation class</b>	II
<b>Voltage (V)</b>	220.00		
<b>Dimmable</b>	No		
<b>Driver</b>	Remote included		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	White/Gold
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	150
<b>Weight (kg)</b>	0.25
<b>Length (mm)</b>	70

### Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Fixed No Trim 2 Spots Optic Medium



---

Pre-installation Frame  
08.0510.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90