


# Light Shadow Fixed No Trim 2 Spots Optic Medium

#### 03.9210.40A - White/White


Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).











Number of heads LED Lamp category Power (W) 5.4W CCT (K) 3000K CRI 90


Net lumen (lm) Mountings Environment

470

Ceiling recessed Indoor dry location

#### Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Medium Beam angle (°) 22 Beam angle C90-270 (°) 22



Luminous flux luminaire 470 lm (EXTREME CUT OFF)

Insulation class

Beam Angle:		22
h(m)	E(lx)	D(m)
1	3139	0.39
2	785	0.78
3	349	1.17
4	196	1.56

126

1.95

5

### **Electrical**

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No

Driver Remote included **Emergency** 

Without

## Physical

Color White/White Orientation Fixed Recessed depth (mm) 150 Weight (kg) 0.25 Length (mm) 70

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 2 Spots Optic Medium





Pre-installation Frame 08.0510.00

Accessory for mounting of No Trim continuous line. 08.0052.90