Ceiling recessed Indoor dry location






03.8853.14A - Black/Black


Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).












•		
Number of heads	1	Net lumen (lm)
Lamp category	LED	Mountings
Power (W)	5.4W	Environment
CCT (K)	2700K	
CRI	90	

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Bear	Beam Angle:	
h(m)	E(l x)	D(m)
1	7883	0.18
2	1971	0.36
3	876	0.54
4	493	0.72
5	315	0.90

Luminous flux luminaire 437 lm (EXTREME CUT OFF)

	lectrica.	ı
_	00tr100	ı

Frequency (Hz)	50/60	Insulation class	Ш
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

Physical

Color	Black/Black
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 2 Spots Optic Spot





Pre-installation Frame 08.0510.00

Accessory for mounting of No Trim continuous line. 08.0052.90