

Light Shadow Fixed No Trim 2 Spots Optic Spot



Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).





- 2 -		
	51x86 12, 12, 12, 12, 12, 12, 12, 12, 12, 12,	i 5




Main	specifications

Number of heads	1	Net lumen (lm)	444
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



h(m)	E(lx)	D(m)	
1	7851	0.18	
2	1963	0.36	
3	872	0.55	
4	491	0.73	
5	314	0.91	

Beam Angle:

10°

Luminous flux luminaire 444 lm (EXTREME CUT OFF)

lactrical

Frequency (Hz)	50/60	Insulation class	П
Voltage (V)	220.00		
Dimmable	No		
Driver	Romoto included		

Without

Emergency Physical

Color	Black/Gold
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 2 Spots Optic Spot





Pre-installation Frame 08.0510.00

Accessory for mounting of No Trim continuous line. 08.0052.90