

03.8856.40A - White/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).





51x86	+
 	12,5
	3[[8
70 <b></b>	
	255



1/1/2	in sp	$\sim$	こつつきに	anc
ועום	III SL		IL COLL	เมเธ
	-			•

Number of heads LED Lamp category Power (W) 5.4W CCT (K) 3000K CRI 90


Net lumen (lm) Mountings

475

Ceiling recessed Environment Indoor dry location

### Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10



E(lx) h(m) D(m) 8680 0.17 2 2170 0.35 3 0.52 964 4 542 0.70 5 347 0.87

Beam Angle:

10°

Luminous flux luminaire 475 lm (EXTREME CUT OFF)

Insulation class

### **Electrical**

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No Driver

Remote included

Without

## Physical

**Emergency** 

White/White Orientation Fixed Recessed depth (mm) 150 Weight (kg) 0.25 Length (mm) 70

## Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 2 Spots Optic Spot





Pre-installation Frame 08.0510.00

Accessory for mounting of No Trim continuous line. 08.0052.90