Beam Angle:

h(m)

2

E(lx)

8393

2098

10°

D(m)

0.18

0.36



Light Shadow Fixed No Trim 2 Spots Optic Spot

03.8858.14A - Black/Chrome

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).





-25	
	51x86 12,5 12,5 51x86 12,5 51x86 12,5




Main	specifications

Number of heads LED Lamp category Power (W) 5.4W CCT (K) 3000K CRI 90

Net lumen (lm) Mountings Ceiling recessed Environment Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10



(EXTREME CUT OFF)

477 lm

3 0.55 933 4 525 0.73 5 336 0.91

50/60 Insulation class Frequency (Hz) Voltage (V) 220.00 Dimmable No Driver Remote included

Without

Physical

Emergency

Color Black/Chrome Orientation Fixed Recessed depth (mm) 150 Weight (kg) 0.25 Length (mm) 70

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 2 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0510.00