


Light Shadow Fixed No Trim 2 Spots Optic Wide Flood

03.8350.40A - White/White

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	443
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle:	46°		
h(m)	E(lx)	D(m)	
1	841	0.84	
2	210	1.69	
3	93	2.53	
4	53	3.38	
5	34	4.22	

Luminous flux luminaire
443 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	No		
Driver	Remote		
Driver type	Electronic		

Physical

Color	White/White
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Fixed No Trim 2 Spots Optic Wide Flood



Accessory for mounting of No Trim
continuous line.
08.0052.90

Pre-installation Frame
08.0510.00