


Light Shadow Fixed No Trim 2 Spots Optic Wide Flood

03.8352.40A - White/Chrome

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




Main specifications

| | | | |
|------------------------|-------|-----------------------|------------------|
| Number of heads | 1 | Net lumen (lm) | 446 |
| Lamp category | LED | Mountings | Ceiling recessed |
| Power (W) | 5.4W | Environment | Indoor |
| CCT (K) | 2700K | | |
| CRI | 90 | | |

Optical

| | |
|-------------------------------|------------|
| Lighting type | Direct |
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Wide flood |
| Beam angle (°) | 44 |
| Beam angle C90-270 (°) | 44 |



| | | | |
|--------------------|-------------|--------------|-------------|
| Beam Angle: | 44° | | |
| | h(m) | E(lx) | D(m) |
| | 1 | 929 | 0.80 |
| | 2 | 232 | 1.60 |
| | 3 | 103 | 2.40 |
| | 4 | 58 | 3.19 |
| | 5 | 37 | 3.99 |

Luminous flux luminaire
446 lm (EXTREME CUT OFF)

Electrical


| | | | |
|-----------------------|------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 220.00 | Insulation class | II |
| Dimmable | No | | |
| Driver | Remote | | |
| Driver type | Electronic | | |

Physical

| | |
|----------------------------|--------------|
| Color | White/Chrome |
| Orientation | Fixed |
| Recessed depth (mm) | 150 |
| Weight (kg) | 0.25 |
| Length (mm) | 70 |

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Fixed No Trim 2 Spots Optic Wide Flood



Accessory for mounting of No Trim
continuous line.
08.0052.90

Pre-installation Frame
08.0510.00