

## Light Shadow Fixed No Trim 2 Spots Optic Wide Flood

■ 03.8355.40A - White/Black

Recessed integrated luminaire with 2 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

Number of heads	1	Net lumen (lm)	464
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	5.4W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle: 46°

h(m)	E(lx)	D(m)
1	881	0.84
2	220	1.69
3	98	2.53
4	55	3.38
5	35	4.22

Luminous flux luminaire  
464 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		


### Physical

Color	White/Black
Orientation	Fixed
Recessed depth (mm)	150
Weight (kg)	0.25
Length (mm)	70

### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 2 Spots Optic Wide Flood



Pre-installation Frame  
08.0510.00

Accessory for mounting of No Trim  
continuous line.  
08.0052.90