




03.9222.40A - White/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).











Number of neads	1
amp category	LED
Power (W)	10.8W
CCT (K)	2700K
CRI	90


Net lumen (lm) Mountings Environment

752 Ceiling recessed

Indoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Luminous flux luminaire 752 lm (EXTREME CUT OFF)

Insulation class

Beam Angle:		22°
h(m)	E(lx)	D(m)
1	5060	0.39
2	1265	0.77
3	562	1.16
4	316	1.55
5	202	1.94

Electrical

Frequency (Hz)	50/60
Voltage (V)	220.00
Dimmable	No
Driver	Remote included

Without

Physical

Emergency

Color	White/Chrom
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 4 Spots Optic Medium





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90