




03.9230.14A - Black/White


Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).











 Number of heads
 1

 Lamp category
 LED

 Power (W)
 10.8W

 CCT (K)
 3000K


 CRI
 90

Net lumen (lm) Mountings Environment 793

Ceiling recessed Indoor dry location

## Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Medium
Beam angle (°) 22
Beam angle C90-270 (°) 22



Luminous flux luminaire 793 lm (EXTREME CUT OFF)

Beam Angle:		22°
h(m)	E( <b>l</b> x)	D(m)
1	5302	0.39
2	1325	0.78
3	589	1.17
4	331	1.56

212 1.95

5

## Electrical

Frequency (Hz) 50/60 Insulation class
Voltage (V) 220.00
Dimmable No
Driver Remote included

Without

Emergency Physical

Color Black/White
Orientation Fixed
Recessed depth (mm) 75
Weight (kg) 0.34
Length (mm) 140

## Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Fixed No Trim 4 Spots Optic Medium





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0511.00