


03.9231.14A - Black/Black

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).









N/	nın	cna	ヘルナルヘイ	ations
ıv	alli	200		11111115
	• • • • •	-	••	

Number of heads LED Lamp category Power (W) 10.8W CCT (K) 3000K CRI 90


Net lumen (lm) Mountings Environment

793

Ceiling recessed Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Medium Beam angle (°) 22 Beam angle C90-270 (°) 22



Luminous flux luminaire 793 lm (EXTREME CUT OFF)

Insulation class

Bean	22°	
h(m)	E(lx)	D(m)
1	5425	0.39
2	1356	0.78
3	603	1.17
4	339	1.56

217

1.95

5

Electrical

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No

Driver Remote included **Emergency**

Without

Physical

Color Black/Black Orientation Fixed Recessed depth (mm) 75 Weight (kg) 0.34 Length (mm) 140

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 4 Spots Optic Medium





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90