

## Light Shadow Fixed No Trim 4 Spots Optic Medium

03.9232.14A - Black/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                        |       |                       |                     |
|------------------------|-------|-----------------------|---------------------|
| <b>Number of heads</b> | 1     | <b>Net lumen (lm)</b> | 802                 |
| <b>Lamp category</b>   | LED   | <b>Mountings</b>      | Ceiling recessed    |
| <b>Power (W)</b>       | 10.8W | <b>Environment</b>    | Indoor dry location |
| <b>CCT (K)</b>         | 3000K |                       |                     |
| <b>CRI</b>             | 90    |                       |                     |


### Optical

|                               |           |
|-------------------------------|-----------|
| <b>Lighting type</b>          | Direct    |
| <b>LED type</b>               | Power LED |
| <b>Light distribution</b>     | Symmetric |
| <b>Optical type</b>           | Medium    |
| <b>Beam angle (°)</b>         | 22        |
| <b>Beam angle C90-270 (°)</b> | 22        |



|                    |              |             |  |
|--------------------|--------------|-------------|--|
| <b>Beam Angle:</b> | 22°          |             |  |
| <b>h(m)</b>        | <b>E(lx)</b> | <b>D(m)</b> |  |
| 1                  | 5397         | 0.39        |  |
| 2                  | 1349         | 0.77        |  |
| 3                  | 600          | 1.16        |  |
| 4                  | 337          | 1.55        |  |
| 5                  | 216          | 1.94        |  |

Luminous flux luminaire  
802 lm (EXTREME CUT OFF)



### Electrical

|                       |                 |                         |    |
|-----------------------|-----------------|-------------------------|----|
| <b>Frequency (Hz)</b> | 50/60           | <b>Insulation class</b> | II |
| <b>Voltage (V)</b>    | 220.00          |                         |    |
| <b>Dimmable</b>       | No              |                         |    |
| <b>Driver</b>         | Remote included |                         |    |
| <b>Emergency</b>      | Without         |                         |    |

### Physical


|                            |              |
|----------------------------|--------------|
| <b>Color</b>               | Black/Chrome |
| <b>Orientation</b>         | Fixed        |
| <b>Recessed depth (mm)</b> | 75           |
| <b>Weight (kg)</b>         | 0.34         |
| <b>Length (mm)</b>         | 140          |



### Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Fixed No Trim 4 Spots Optic Medium



---

Pre-installation Frame  
08.0511.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90