
Ceiling recessed

Indoor dry location








Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).










# Main specifications

Number of heads	1	Net lumen (lm)
Lamp category	LED	Mountings
Power (W)	10.8W	Environment
CCT (K)	3000K	
CDI	00	

# Optical

ighting type	Direct
ED type	Power LED
ight distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



<u> </u>		·	V
Lumin	ous fl	ux lur	ninaire
788 lm	(FXT	REME (	CUT OFF)

Beam Angle:		22°
h(m)	E(lx)	D(m)
1	5266	0.39
2	1316	0.78
3	585	1.17

211

1.56

1.95

#### **Electrical**

Frequency (Hz)	50/60	Insulation class	- 1
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		

Without

## Physical

**Emergency** 

Color	Black/Gold
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 4 Spots Optic Medium





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90