




03.8860.14A - Black/White

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).









Main	specifications

Number of heads LED Lamp category Power (W) 10.8W CCT (K) 2700K CRI 90

Net lumen (lm) Mountings Environment

Ceiling recessed

Indoor dry location

#### Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10

90°
606 ///// > 606
100/ >/    > 1
X X
N / T \ M
$30^{\circ}$ $13743 \text{ cd}$ $30^{\circ}$
50 / 13/43 Cd / 30 ]
Luminous flux luminairo

Insulation class

Luminous flux luminaire 751 lm (EXTREME CUT OFF)

	Bea	m Angle:	10°
90°	h(m	) E(lx)	D(m)
600	1	13743	0.17
	2	3436	0.35
	3	1527	0.52
	4	859	0.70
$\sqrt{13743} \text{ cd} \sqrt{30^\circ}$	5	550	0.87

## **Electrical**

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No Driver

Remote included Without

# Physical

**Emergency** 

Color Black/White Orientation Fixed Recessed depth (mm) 75 Weight (kg) 0.34 Length (mm) 140

### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 4 Spots Optic Spot





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90