


03.8861.14A - Black/Black


Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).











 Number of heads
 1

 Lamp category
 LED

 Power (W)
 10.8W

 CCT (K)
 2700K


 CRI
 90

Net lumen (lm) Mountings Environment 724

Ceiling recessed Indoor dry location

## Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Spot
Beam angle (°) 10
Beam angle C90-270 (°) 10



Luminous flux luminaire
724 lm (EXTREME CUT OFF)

Insulation class

Beam Angle:		10°
h(n	n) E( <b>l</b> x)	D(m)
1_	13076	0.18
2	3269	0.36
3	1453	0.54
4	817	0.72
5	523	0.90

## Electrical

 Frequency (Hz)
 50/60

 Voltage (V)
 220.00

 Dimmable
 No

Driver Remote included Emergency Without

# Physical

ColorBlack/BlackOrientationFixedRecessed depth (mm)75Weight (kg)0.34Length (mm)140

#### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 4 Spots Optic Spot





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90