




03.8865.14A - Black/Black

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).









| M | ain | speci | fications | |
|---|-----|-------|-----------|--|
| | | | | |


Number of heads LED Lamp category Power (W) 10.8W CCT (K) 3000K CRI 90

Net lumen (lm) 773 Mountings Environment

Ceiling recessed Indoor dry location

Optical

Lighting type Direct LED type Power LED Light distribution Symmetric Optical type Spot Beam angle (°) 10 Beam angle C90-270 (°) 10



Luminous flux luminaire 773 lm (EXTREME CUT OFF)

Insulation class

| Ве | am Angle: | 10° |
|-----|-----------|------|
| h(n | n) E(lx) | D(m) |
| 1_ | 13948 | 0.18 |
| 2 | 3487 | 0.36 |
| 3 | 1550 | 0.54 |
| 4 | 872 | 0.72 |
| 5 | 558 | 0.90 |

Electrical

Frequency (Hz) 50/60 Voltage (V) 220.00 Dimmable No Driver

Remote included **Emergency**

Without

Physical

Color Black/Black Orientation Fixed Recessed depth (mm) 75 Weight (kg) 0.34 Length (mm) 140

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 4 Spots Optic Spot





Pre-installation Frame 08.0511.00

Accessory for mounting of No Trim continuous line. 08.0052.90