


## Light Shadow Fixed No Trim 4 Spots Optic Wide Flood

03.8364.40A - White/Chrome

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

Number of heads	1	Net lumen (lm)	789
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	10.8W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	44
Beam angle C90-270 (°)	44



Beam Angle: 44°

h(m)	E(lx)	D(m)
1	1644	0.80
2	411	1.60
3	183	2.40
4	103	3.19
5	66	3.99

Luminous flux luminaire  
789 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		


### Physical

Color	White/Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.34
Length (mm)	140

### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 4 Spots Optic Wide Flood



Accessory for mounting of No Trim  
continuous line.  
08.0052.90

Pre-installation Frame  
08.0511.00