


## Light Shadow Fixed No Trim 8 Spots Optic Flood

03.9247.14A - Black/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

Number of heads	1	Net lumen (lm)	1814
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	5618	0.60
2	1405	1.19
3	624	1.79
4	351	2.38
5	225	2.98

Luminous flux luminaire  
1814 lm (EXTREME CUT OFF)

### Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

### Physical



Color	Black/Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

### Note

It requires a pre-installation frame, to be ordered separately.



# Light Shadow Fixed No Trim 8 Spots Optic Flood



Accessory for mounting of No Trim  
continuous line.  
08.0052.90

Pre-installation Frame  
08.0512.00