



Light Shadow Fixed No Trim 8 Spots Optic Flood

03.9247.40A - White/Chrome

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	1814
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Flood
Beam angle (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	5618	0.60
2	1405	1.19
3	624	1.79
4	351	2.38
5	225	2.98

Luminous flux luminaire
1814 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

Physical

Color	White/Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

Note


It requires a pre-installation frame, to be ordered separately.



Light Shadow Fixed No Trim 8 Spots Optic Flood



Accessory for mounting of No Trim
continuous line.
08.0052.90



Pre-installation Frame
08.0512.00