
1781

Ceiling recessed

Indoor dry location









Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).












Number of neads	1
Lamp category	LED
Power (W)	21.6W
CCT (K)	2700K
CRI	90

Optical

ighting type	Direct
LED type	Power LED
ight distribution	Symmetric
Optical type	Medium
Beam angle (°)	22
Beam angle C90-270 (°)	22



Net lumen (lm)

Mountings

Environment

JOU		11.	702	cat	30
Lum	ino	us	flux	lum	inaire
1781	lm	(E)	KTREN	ME CU	T OFF)

Angle:	22°
E(l x)	D(m)
1982	0.39
2995	0.77
1331	1.16
	E(lx) 1982 2995

1.55

479 1.94

Electrical

Frequency (Hz)	50/60	Insulation class	Ш
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		

Without

Emergency Physical

Color	White/Gold
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 8 Spots Optic Medium





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0512.00