


## Light Shadow Fixed No Trim 8 Spots Optic Spot

■ 03.8873.40A - White/Black

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

|                 |       |                |                     |
|-----------------|-------|----------------|---------------------|
| Number of heads | 1     | Net lumen (lm) | 1830                |
| Lamp category   | LED   | Mountings      | Ceiling recessed    |
| Power (W)       | 21.6W | Environment    | Indoor dry location |
| CCT (K)         | 3000K |                |                     |
| CRI             | 90    |                |                     |

### Optical

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| LED type               | Power LED |
| Light distribution     | Symmetric |
| Optical type           | Spot      |
| Beam angle (°)         | 10        |
| Beam angle C90-270 (°) | 10        |



Beam Angle: 10°

| h(m) | E(lx) | D(m) |
|------|-------|------|
| 1    | 33034 | 0.18 |
| 2    | 8259  | 0.36 |
| 3    | 3670  | 0.54 |
| 4    | 2065  | 0.72 |
| 5    | 1321  | 0.90 |

Luminous flux luminaire  
1830 lm (EXTREME CUT OFF)

### Electrical

|                |                 |                  |    |
|----------------|-----------------|------------------|----|
| Frequency (Hz) | 50/60           | Insulation class | II |
| Voltage (V)    | 220.00          |                  |    |
| Dimmable       | No              |                  |    |
| Driver         | Remote included |                  |    |
| Emergency      | Without         |                  |    |



### Physical

|                     |             |
|---------------------|-------------|
| Color               | White/Black |
| Orientation         | Fixed       |
| Recessed depth (mm) | 75          |
| Weight (kg)         | 0.50        |
| Length (mm)         | 280         |

### Note

It requires a pre-installation frame, to be ordered separately.

# Light Shadow Fixed No Trim 8 Spots Optic Spot



---

Pre-installation Frame  
08.0512.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90