


Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).









Main specifications


Number of heads	1
amp category	LED
Power (W)	21.6W
CCT (K)	3000K
CRI	90

Net lumen (lm) Mountings 1906 Ceiling recessed

MountingsCeiling recessedEnvironmentIndoor dry location

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10



Luminous flux luminaire 1906 lm (EXTREME CUT OFF)

Beam Angle:		10°
h(n	n) E(lx)	D(m
1	33574	0.18
2	8394	0.36
3	3730	0.55
4	2098	0.73
5	13//3	∩ Q1

Electrical

Frequency (Hz)	50/60	Insulation class
Voltage (V)	220.00	
Dimmable	No	
Driver	Remote included	

Without

Physical

Emergency

Color	Black/Chrome
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 8 Spots Optic Spot





Accessory for mounting of No Trim continuous line. 08.0052.90

Pre-installation Frame 08.0512.00