

Light Shadow Fixed No Trim 8 Spots Optic Wide Flood**03.8366.14A - Black/White**


Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).

**Main specifications**

Number of heads	1	Net lumen (lm)	1763
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	45
Beam angle C90-270 (°)	45



Beam Angle: 45°

h(m)	E(lx)	D(m)
1	3286	0.83
2	822	1.67
3	365	2.50
4	205	3.34
5	131	4.17

Luminous flux luminaire
1763 lm (EXTREME CUT OFF)**Electrical**

Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

Physical

Color	Black/White
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280


Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 8 Spots Optic Wide Flood



Accessory for mounting of No Trim
continuous line.
08.0052.90



Pre-installation Frame
08.0512.00