




03.8367.14A - Black/Black

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).











 Number of heads
 1

 Lamp category
 LED

 Power (W)
 21.6W

 CCT (K)
 2700K

 CRI
 90


Net lumen (lm) Mountings Environment

1773 Ceiling red

Ceiling recessed Indoor dry location

Optical

Lighting type
Direct
Power LED
Light distribution
Optical type
Beam angle (°)
Beam angle C90-270 (°)
Direct
Power
Wide flood
46
Beam 46



Luminous flux luminaire 1773 lm (EXTREME CUT OFF)

Insulation class

Beam Angle:		46°
h(m)	E(l x)	D(m)
1	3363	0.84
2	841	1.69
3	374	2.53
4	210	3.38
5	135	4.22

Electrical

 Frequency (Hz)
 50/60

 Voltage (V)
 220.00

 Dimmable
 No

 Driver
 Remote includes

Remote included Without

Physical

Emergency

ColorBlack/BlackOrientationFixedRecessed depth (mm)75Weight (kg)0.50Length (mm)280

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim 8 Spots Optic Wide Flood





Pre-installation Frame 08.0512.00

Accessory for mounting of No Trim continuous line. 08.0052.90