


Light Shadow Fixed No Trim 8 Spots Optic Wide Flood

03.8373.14A - Black/Gold

Recessed integrated luminaire with 8 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	1809
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	21.6W	Environment	Indoor dry location
CCT (K)	3000K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Wide flood
Beam angle (°)	46
Beam angle C90-270 (°)	46



Beam Angle:	46°		
h(m)	E(lx)	D(m)	
1	3333	0.84	
2	833	1.69	
3	370	2.53	
4	208	3.38	
5	133	4.22	

Luminous flux luminaire
1809 lm (EXTREME CUT OFF)

Electrical


Frequency (Hz)	50/60	Insulation class	II
Voltage (V)	220.00		
Dimmable	No		
Driver	Remote included		
Emergency	Without		

Physical

Color	Black/Gold
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.50
Length (mm)	280

Note

It requires a pre-installation frame, to be ordered separately.



Light Shadow Fixed No Trim 8 Spots Optic Wide Flood



Pre-installation Frame
08.0512.00

Accessory for mounting of No Trim
continuous line.
08.0052.90