

## Light Shadow Fixed No Trim Dali Version 12 Spots Optic Flood

■ □ 03.9275.14ADA - Black/White

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




### Main specifications

<b>Number of heads</b>	1	<b>Net lumen (lm)</b>	2836
<b>Lamp category</b>	LED	<b>Mountings</b>	Ceiling recessed
<b>Power (W)</b>	32.4W	<b>Environment</b>	Indoor
<b>CCT (K)</b>	3000K		
<b>CRI</b>	90		

### Optical


<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Flood
<b>Beam angle (°)</b>	33
<b>Beam angle C90-270 (°)</b>	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	8841	0.59
2	2210	1.18
3	982	1.78
4	553	2.37
5	354	2.96


Luminous flux luminaire  
2836 lm (EXTREME CUT OFF)



### Electrical

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	220.00	<b>Insulation class</b>	II
<b>Dimmable</b>	Yes		
<b>Driver</b>	Remote		
<b>Driver type</b>	Electronic dimmable push, Electronic dimmable DALI		

### Certification / Marking



### Physical

<b>Color</b>	Black/White
<b>Orientation</b>	Fixed
<b>Recessed depth (mm)</b>	75
<b>Weight (kg)</b>	0.66
<b>Length (mm)</b>	420

### Note

It requires a pre-installation frame, to be ordered separately.

## Light Shadow Fixed No Trim Dali Version 12 Spots Optic Flood



---

Pre-installation Frame  
08.0513.00

---

Accessory for mounting of No Trim  
continuous line.  
08.0052.90