



Light Shadow Fixed No Trim Dali Version 12 Spots Optic Spot

03.8879.40ADA - White/Gold

Recessed integrated luminaire with 12 LED lighting spots. Remote power supply included (220-240V).




Main specifications

Number of heads	1	Net lumen (lm)	2668
Lamp category	LED	Mountings	Ceiling recessed
Power (W)	32.4W	Environment	Indoor
CCT (K)	2700K		
CRI	90		

Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Spot
Beam angle (°)	10
Beam angle C90-270 (°)	10




Beam Angle:	10°		
	h(m)	E(lx)	D(m)
	1	47225	0.18
	2	11806	0.36
	3	5247	0.55
	4	2952	0.73
	5	1889	0.91

Luminous flux luminaire
2668 lm (EXTREME CUT OFF)

Electrical

Frequency (Hz)	50/60	Emergency	Without
Voltage (V)	220.00	Insulation class	II
Dimmable	Yes		
Driver	Remote		
Driver type	Electronic dimmable push, Electronic dimmable DALI		

Certification / Marking




Physical

Color	White/Gold
Orientation	Fixed
Recessed depth (mm)	75
Weight (kg)	0.66
Length (mm)	420

Note

It requires a pre-installation frame, to be ordered separately.

Light Shadow Fixed No Trim Dali Version 12 Spots Optic Spot



Pre-installation Frame
08.0513.00

Accessory for mounting of No Trim
continuous line.
08.0052.90